

**ACTION TAKEN REPORT (ATR) OF GUJARAT POLLUTION CONTROL BOARD  
IN COMPLIANCE OF HON'BLE NGT WESTERN ZONE BENCH, PUNE IN THE  
MATTER OF ORIGINAL APPLICATION NO. 05 OF 2024 (WZ) WRT LETTER  
PETITION NO. 74 OF 2023 (COMPLAINT DATED 13.12.2023)**

**(I) PREAMBLE**

Hon'ble the National Green Tribunal, Western Zone Bench, At Pune Vide Original Application No. 05 OF 2024 (WZ) took cognizance of Complaint dated 13.12.2023 made by the Azad Hind Mazdoor Company, A.K. Road, Fulpada, Surat, alleging that Arya Processors Pvt. Ltd located at Block No. 279, Baleshwar, Palsana, Gujarat is releasing untreated wastewater directly in open drain and is also emitting black polluted smoke in open air because of the use of restricted burn wood, wooden coal, chindhi, waste fabrics, plastic material, silk cloths, etc. For burning in the mill boiler, leading to huge pollution, resulting in health hazards to the local residents.

Hon'ble NGT issued the following Direction as per order 02/01/2024

*Relevant Para 2, is reproduced as “Considering the facts stated in the complaint, we deem it appropriate to call for a report from the Member Secretary, Gujarat Pollution Control Board (GPCB) as to the truthfulness of the content of the aforesaid complaint and the action taken there end, if any, within four weeks.”*

**(II) BASIC INFORMATION OF INDUSTRY**

- M/s. Arya Processors is a textile industry which engaged in Dyeing of Art Silk Cloth activity at Plot No. 279, N.H. No. 8, Baleshwar – 394 315, Ta: Palsana, Dist: Surat.
- Unit having Consent to Operate/Consolidate Consent and Authorisation (CTO/CC&A) of the Board, which is valid up to date: 31/03/2026 for the manufacturing of “Dyeing of Art Silk Cloth” having total production quantity: 1,25,000 Meters/Day. [**Copy of CTO/CC&A is annexed herewith and marked as “Annexure – A”**]

**(III) THE INSPECTION OF ABOVE MENTION UNIT WAS CARRIED OUT BY THE REGIONAL OFFICE, SURAT OF GUJARAT POLLUTION CONTROL BOARD AND AS PER THE INSPECTION REPORT DATED: 01/02/2024 OBSERVATION/ FACTUAL DETAILS ARE AS UNDER:**

- During visit production plant is observed in operation and production of Dying of Art silk Cloth is going on. Source of water supply is from own Bore well. Generated industrial w/w is partly reused in drum washing & scrubbers, while remaining is collected in collection cum settling tank & after passing through bar screen, it is discharged in to CETP -GETPL for further treatment & disposal. Unit is member of CETP-GETPL. During visit one wastewater sample is collected from final outlet of industry, details are as per data sheet.
- Flow meter provided at outlet discharge line and reading noted as: Totalizer- 281257.48 M3. During visit no any w/w discharged is outside of the premises. Domestic waste water disposed in to soak pit system/septic tank system.
- Unit has provided steam Boiler (capacity 6 TPH) and TFH (capacity 1500 U) attached with common stack. Unit has provided MCS, Bag filter followed by alkali water scrubber as APCM with Boiler and MCS, Bag filter followed by alkali water scrubber as APCM with TFH. Imported coal is used as a fuel (Copy attached herewith) with mechanized auto fuel feeding system.
- During visit Boiler, TFH and provided all APCMs are found in operation. One flue gas stack sample is collected from common stack attached to boiler and TFH; details are as per data sheet. CEMS provided at stack for PM is recorded as: PM – 29.0 kg/hr. Unit has provided D. G. Set of 380 KVA as standby.
- During visit ETP sludge: @ 150 Kg & Discarded containers: 25 Nos are observed in storage area. @ 30 MT Imported Coal found stored in boiler area. During inspection ambient air quality is observed normal within premises as well as surrounding area.

**[Copy of Inspection Report is annexed herewith and marked as “Annexure – B”]**

**ANALYSIS RESULTS OF COLLECTED SAMPLES**

<b><u>Final outlet of industry</u></b>		
<b><u>Parameters</u></b>	<b><u>Results</u></b>	<b><u>Norms</u></b>
pH	6.40	6.5 to 8.5
Colour	30	100
Total Dissolved Solids (TDS)	2080	2100
Suspended Solids (SS)	132	300
Chloride	590	600
Chemical Oxygen Demand (COD)	985	1000
Biological Oxygen Demand (BOD)	285	400
<b>****All the parameters in mg/L except pH and Colour</b>		

<b><u>Common Stack attached to Boiler &amp; TFH (Thermic Fluid Heater) through APCM</u></b>		
<b><u>Parameters</u></b>	<b><u>Results</u></b>	<b><u>Norms</u></b>
PM (Particulate Matter)	143 mg/NM <sup>3</sup>	150 mg/NM <sup>3</sup>
SO <sub>2</sub>	4.24 PPM	100 PPM
NO <sub>x</sub>	2.14 PPM	50 PPM

[Copy of Analysis Reports are annexed herewith and marked as “Annexure – C”]

**CONCLUSION:**

Looking at the representations of the complainer and inspection report as well as collected samples analysis reports, no violation/non-compliance observed as per the content of the complainer and unit is found in compliance of CCA issued by this Board.

The Board has published Gazetted Notifications for the use of solid fuels in industrial utilities, and the fire wood was included in the list of approved fuels. The copy of Gazetted Notification published by the Board are annexed herewith and marked as “Annexure – D”.

*“We regret for not submit action taken report in time”*

## GUJARAT POLLUTION CONTROL BOARD

PARYAVARAN BHAVAN

Sector-10-A, Gandhinagar-382 010

Phone : (079) 23226295

Fax : (079) 23232156

Website : www.gpcb.gov.in



GPCB

By R.P.A.D

In exercise of the power conferred under section-25 of the Water (Prevention and Control of Pollution) Act-1974, under section-21 of the Air (Prevention and Control of Pollution)-1981 and Authorization under rule 6(2) of the Hazardous And Other Waste (Management and Transboundary) Rules, 2016 framed under the Environmental (Protection) Act-1986. This Board is empowered to Grant CC&A.

And whereas Board has received consolidated consent application letter no. 44366 dated 31-07-2021 for the Consolidated Consent and Authorization (CC & A) of this Board under the provisions / rules of the aforesaid Acts. Consents & Authorization are hereby granted as under:

**CONSENTS AND AUTHORISATION:**

(Under the provisions /rules of the aforesaid environmental acts)

To,  
M/s. Aarya processors (Old Name:- Sheetal Nath Silk Mill)  
Block No: 279, N.H.No. 8,  
Baleshwar-394315,  
Tal: Palsana, Dist: Surat.

1. Consent Order No. AWH-114037 Date of issue: 31-03-2026.
2. The consents shall be valid upto 31-03-2026 for the use of outlet for the discharge of treated effluent and emission due to operation of industrial plant for manufacturing of the following items/ products:

Sr. No.	Product	Quantity
1	Dyeing of Art Silk Cloth	1,25,000 Meters/Day

**Subject to specific condition:**

1. Give compliance of coal handling guidelines and provide alkali scrubber looking to quantum of coal being used boiler/Thermopack capacity within three month at Regional Office and Head Office.
2. Industry shall obtain NOC from CGWA as per order of Hon. National Green Tribunal for the withdrawal of ground water and you shall strictly comply with condition of NOC granted from CGWA.
3. Industry shall manage Solid Wastes generated from industrial activities as per Solid Waste Management Rules-2016 (solid waste as defined in Rule-3(46)).
4. As per Provisions of Rule 18 of Solid Waste Management Rules-2016 you are directed to make an arrangement in Utilities to replace at least five percent (5%) of your solid fuel requirement by 'refused derived fuel'.
5. Industry shall provide dedicated storage facility for fly ash.
6. Industry shall comply with fly ash notification 1999 as amended from time to time.

M/s. Aarya processors (Old Name:- Sheetal Nath Silk Mill).(ID\_26808)

Page 1 of 8

*Clean Gujarat Green Gujarat*

ISO - 9001 - 2008 &amp; ISO - 14001 - 2004 Certified Organisation

Outward No: 59738

### 3. CONDITIONS UNDER THE WATER ACT:

- 3.1. Source of Water:- Borewell.
- 3.2. The quantity of the fresh water consumption for industrial purpose shall not exceed 1200 KL/Day.
- 3.3. The quantity of the fresh water consumption for domestic purpose shall not exceed 20 KL/Day.
- 3.4. The quantity of the industrial effluent to be generated from the manufacturing process and other ancillary industrial operations shall not exceed 1000 KL/Day.( Total Booked load in CETP: 1000 KL/Day)
- 3.5. The quantity of domestic waste water shall not exceed 20 KL/Day.
- 3.6. Domestic effluent shall be disposed off through septic tank/soak pit system.
- 3.7. The applicant shall operate effluent treatment system efficiently so that effluent from the industrial unit shall conform to the CETP inlet norms mentioned below however the final discharge of treated effluent from CETP shall adhere to the prescribed standards for CETP of M/s. Gujarat Eco Textile Park Ltd(GETPL).

PARAMETERS	CETP INLET NORMS
PH	6.5 TO 8.5
Temperature	40 <sup>o</sup> C
Colour (pt.co.scale) in units	100 units
Suspended Solids	300 mg/l
Oil and Grease	10 mg/l
Phenolic Compounds	1 mg/l
Sulphides	2 mg/l
Ammonical Nitrogen	50 mg/l
Total Chromium	2 mg/l
Hexavalent Chromium	0.1 mg/l
BOD (5 days at 20 <sup>o</sup> C)	400 mg/l
COD	1000 mg/l
Total Dissolved Solids	2100 mg/l

- 3.8. The final treated effluent conforming to the above standards shall be fully conveyed into CETP of M/s. Gujarat Eco Textile Park Ltd(GETPL). through tanker of GETPL & in no case effluent shall be discharged in to Environment by any means.
- 3.9. In case of failure of CETP, applicant shall have to treat the trade effluent of their unit fully so as to achieve the quality of the treated effluent from their industrial premises as per the GPCB norms mentioned below:-

PARAMETERS	CETP OUTLET NORMS
PH	6.5 TO 8.5
Temperature	40 <sup>o</sup> C
Suspended Solids	100 mg/l
Oil and Grease	10 mg/l
Phenolic Compounds	1 mg/l
Sulphides	2.0 mg/l
Ammonical Nitrogen	50 mg/l
Total Chromium	2 mg/l
Hexavalent Chromium	0.1 mg/l



# 12 GUJARAT POLLUTION CONTROL BOARD

PARYAVARAN BHAVAN

Sector-10-A, Gandhinagar-382 010

Phone : (079) 23226295

Fax : (079) 23232156

Website : www.gpcb.gov.in

BOD (5 days at 20°C)	30 mg/l
COD	250 mg/l
Chlorides	600 mg/l
Sulphate	1000 mg/l
Bio-assay test	90 % Survival of fish after 96 hours in 100 % effluent
Fixed Dissolved Solids	2100 mg/l

**OR**

The applicant shall either stop or curtail its production activities if the effluent is not adequately treated by the CETP of GETPL to conform to the standards specified by G.P.C.B.

- 3.10. The applicant shall be responsible for conveyance of entire treated effluent to the CETP of M/s. GETPL & due care shall be taken to avoid any leakage or spillage of effluent during conveyance of treated effluent through drain.
- 3.11. Unit shall provide flow meters at inlet & outlet of ETP & maintain its record.
- 3.12. The applicant shall inform renewal/termination of CETP membership well in advance to GPCB.
- 3.13. The applicant shall be required to make storage facilities to store the primary treated effluent for at least 48 hours by providing acid proof brick lined impervious tanks/HDPE tanks.
- 3.14. The applicant shall make fixed arrangement for loading the effluent after primary treatment to the CETP. The unit shall not keep any by-pass line or system or loose or flexible pipe line for discharging effluent into the tanker of GETPL.
- 3.15. Leachate from the hazardous solid waste, if any shall also be connected into a collection tank through leachate collection facilities and shall be conveyed alongwith industrial effluent to the CETP of GETPL.
- 3.16. Magnetic flow meters shall be installed at the inlet & outlet of effluent collection tanks/ETP to measure the quantity of effluent discharging in to underground drainage system of GETPL.
- 3.17. The ENTIRE quantity of industrial effluent shall have to be conveyed by GETPL. In no circumstances the effluent either treated or untreated shall be discharged any where else.
- 3.18. Disposal system for storm water shall be provided separately. In no circumstances storm water shall be mixed with the industrial effluent.
- 3.19. GETPL member unit have to modify / improve performance of existing Effluent treatment facilities for efficiency & adequacy in order to comply with prescribed in let standards.
- 3.20. The applicant shall keep accurate records of quantity of production of each product, quantity of water consumption, quantity of effluent generated and consumption of electricity on day to day basis and required to submit the complied record of one month to GPCB & GETPL on or before fifth day of the succeeding month.
- 3.21. In case of shut-down of plant for more than three days for any reason, the GETPL unit member shall intimate to GETPL authority & GPCB well in advance for the better operation & management of CETP.
- 3.22. The authorized representative of GETPL may have right of entry at any time for the purpose of inspection and monitoring the effluent collection facilities/ETP (if required) of the applicant.
- 3.23. If the GETPL authority terminates the membership of the applicant for CETP, the GETPL member unit shall have to close down the manufacturing activities/industrial operation of the process plant immediately until the GETPL membership is resumed.

Page 3 of 8

M/s. Aarya processors (Old Name:- Sheetal Nath Silk Mill).(ID\_26808)

*Clean Gujarat Green Gujarat*

ISO - 9001 - 2008 & ISO - 14001 - 2004 Certified Organisation

- 3.24. The applicant shall put up at the entrance a board displaying GETPLL membership number & date of joining of GETPL, the name of unit, particulars of the products/ process and the name of proprietor/partners /directors of the unit and the electricity consumer number as on the record of GSECL.

#### 4. CONDITIONS UNDER THE AIR ACT:

- 4.1. The following shall be used as a fuel in Steam Boiler, Thermo Pack, and D.G.Set respectively.

Sr. No.	Fuel	Quantity
1	Coal	20 MT/Day
2	Diesel	30 lit/hr

- 4.2. The applicant shall install & operate comprehensive adequate air pollution control system in order to achieve prescribed norms.
- 4.3. The flue gas emission through stack attached to Steam Boiler, Thermo Pack, and D.G.Set shall conform to the following standards:

Stack No.	Stack attached to	Stack height in Meter	Air Pollution Control system	Parameter	Permissible Limit
1	Steam Boiler (6 TPH)	37 (Common Stack)	Multi Cyclone Separator & Bag Filter	Particulate Matter SO <sub>2</sub> NO <sub>x</sub>	150 mg/NM <sup>3</sup> 100 ppm 50 ppm
	Thermopack (1500 U)		Multi Cyclone Separator & Alkali Scrubber	Particulate Matter SO <sub>2</sub> NO <sub>x</sub>	150 mg/NM <sup>3</sup> 100 ppm 50 ppm
2	D.G.Set (380 KVA) Stand b	11		Particulate Matter SO <sub>2</sub> NO <sub>x</sub>	150 mg/NM <sup>3</sup> 100 ppm 50 ppm

- 4.4. There shall be no process emission from the manufacturing process as well as any other ancillary process.
- 4.5. Industry shall take adequate measure to control dusting due to storage, transportation & handling of Coal/Lignite & fly ash.
- 4.6. Industry shall comply with Coal handling guideline of the Board.
- 4.7. Industry shall comply with fly ash notification 1999 as amended from time to time.
- 4.8. The concentration of the following parameters in the ambient air within the premises of the industry and a distance of 10meters from the source) other than the stack/vent) shall not exceed the following levels.

PARAMETERS	PERMISSIBLE LIMIT (Microgram/m <sup>3</sup> )	
	Annual	24 Hrs Average
Particulate Matter-10 (PM <sub>10</sub> )	60	100
Particulate Matter- 2.5 (PM <sub>2.5</sub> )	40	60
SO <sub>2</sub>	50	80
NO <sub>x</sub>	40	80

- 4.9. The applicant shall provide portholes, ladder, platform etc at chimney(s) for monitoring the air emissions and the same shall be open for inspection to/and for use of Board's staff. The chimney(s) vents attached to various sources of emission shall be designed by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.



# 14 GUJARAT POLLUTION CONTROL BOARD

PARYAVARAN BHAVAN

Sector-10-A, Gandhinagar-382 010

Phone : (079) 23226295

Fax : (079) 23232156

Website : www.gpcb.gov.in

- 4.10. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standards in respect of noise to less than 75dB(A) during day time and 70 dB (A) during night time. Daytime is reckoned in between 6a.m. and 10 p.m. and nighttime is reckoned between 10 p.m. and 6 a.m.

## 5. D.G. SETS CONDITIONS

The D.G. Set shall have acoustic enclosure and shall comply with the standards specified at Sr. no. 95 of Schedule-I of the rule-3 of E.P. Rules -1986 and Noise pollution level as per the Air Act-1981.

### D.G. Sets standards:-

The flue gas emission through stack attached to D.G. Sets shall conform to the following standards.

- The minimum height of stack to be provided with each of the generator set shall be  $H=h + 0.2 (KVA)^{1/2}$ , where H= Total stack height in meter, h= height of the building in meters where or by the side of which the generator set is installed.
- Noise from DG set shall be controlled by providing an acoustic enclosure or by treating the room acoustically, at the users end.
- The acoustic enclosure or acoustic treatment of the room shall be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on the higher side ( if the actual ambient noise is on the higher side, it may not be possible to check the performance of the acoustic enclosure/ acoustic treatment. Under such circumstances the performance may be checked for noise reduction up to actual ambient noise level, preferably, in the night time). The measurement for insertion loss may be done at different points at 0.5 m from the acoustic enclosure/room, and the averaged.
- The D.G. Set shall be provided with proper exhaust muffler with insertion loss of minimum 25 dB (A).
- All efforts shall be made to bring down the noise level due to the D.G.Set, outside the premises, within the ambient noise requirements by proper siting and control measures.
- Installation of a D.G. Sets must be strictly in compliance with the recommendations of the D.G.Set manufacturer.
- A proper routine and preventive maintenance procedure for the D.G.Set should be set and followed in consultation with the DG Set manufacture which would help prevent noise levels of the DG Set from deteriorating with use.

## 6. AUTHORIZATION as per HAZARDOUS AND OTHER WASTE (MANAGEMENT AND TRANSBOUNDARY) RULES, 2016 Form-2 [See rule 6 (2)]

Form for grant of authorization for occupier or operator handling Hazardous waste

6.1 Authorization order No:- AWH-114037 date of Issue: 31-03-2026.

6.2 M/s. Aarya processors (Old Name:- Sheetal Nath Silk Mill) is hereby granted an authorization to operate facility for following hazardous wastes on the premises situated at Block No: 279, N.H.No. 8, Baleshwar-394315, Tal: Palsana, Dist: Surat.

Sr. No.	Waste	Quantity MT/Year	Schedule-I/ Category	Facility
1	Chemical Sludge from waste water treatment	0.250	35.3	Collection, Storage, Transportation and disposal at GPCB authorized TSDF Site.

Page 5 of 8

M/s. Aarya processors (Old Name:- Sheetal Nath Silk Mill).(ID\_26808)

*Clean Gujarat Green Gujarat*

ISO - 9001 - 2008 & ISO - 14001 - 2004 Certified Organisation

2	Used Oil	0.450	5.1	Collection, storage, transportation and disposal by selling to Registered re-refiners.
3	Empty barrels/containers/liners contaminated with hazardous chemicals/wastes	0.350	33.1	Collection, storage transportation and disposal to authorized decontaminator

6.3 The authorization shall be valid up to **31-03-2026**.

6.4 The authorization is subject to the conditions stated below and such other conditions as may be specified in the rules from time to time under the Environment (Protection) Act-1986.

6.5 The authorization is granted to operate a facility for collection, storage within factory premises transportation and ultimate disposal of Hazardous wastes as per condition no.6.2 to the industry having valid CCA of this Board.

**7. TERMS AND CONDITIONS OF AUTHORISATION**

7.1. The applicant shall comply with the provisions of the Environment (Protection) Act-1986 and the rules made there under.

7.2. The authorization or its renewal shall be produced for inspection at the request of an officer authorized by the Gujarat Pollution Control Board.

7.3. The persons authorized shall not rent, lend, sell, and transfer or otherwise transport the hazardous wastes without obtaining prior permission of the Gujarat Pollution Control Board.

7.4. Any unauthorized change in personnel, equipment or working conditions as mentioned in the authorization order by the persons authorized shall constitute a breach of this authorization.

7.5. The person authorized shall implement Emergency Response Procedure (ERP) for which this authorization is being granted considering all site specific possible scenarios such as spillages, leakages, fire etc. and their possible impacts and also carry out mock drill in this regard at regular interval of time:

7.6. The person authorized shall comply with the provisions outlined in the Central Pollution Control Board guidelines on "Implementing Liabilities for Environmental Damages due to Handling and Disposal of Hazardous Wastes and Penalty"

7.7. It is the duty of the authorized person to take prior permission of the Gujarat Pollution Control Board to close down the facility.

7.8. An application for the renewal of an authorization shall be made as laid down in rules 6(2) under Hazardous and Other Waste Rules, 2016.

7.9. The imported hazardous and other wastes shall be fully insured for transit as well as for any accidental occurrence and its clean-up operation.

7.10. The record of consumption and fate of the imported hazardous and other wastes shall be maintained.

7.11. The hazardous and other wastes which gets generated during recycling or reuse or recovery or pre-processing or utilization of imported hazardous or other wastes shall be treated and disposed of as per specific conditions of authorization.

7.12. The importer or exporter shall bear the cost of import or export and mitigation of damages if any.

7.13. Any other conditions for compliance as per the Guidelines issued by the Ministry of Environment, Forest and Climate Change or Central Pollution Control Board from time to time.

7.14. The waste generator shall be totally responsible for (i.e. collection, storage, transportation and ultimate disposal) the wastes generated.

*h*



# 16 GUJARAT POLLUTION CONTROL BOARD

PARYAVARAN BHAVAN

Sector-10-A, Gandhinagar-382 010

Phone : (079) 23226295

Fax : (079) 23232156

Website : www.gpcb.gov.in

- 7.15. Records of waste generation, its management and annual return shall be submitted to Gujarat Pollution Control Board in Form-4 by 30<sup>th</sup> day of June of every year for the preceding period April to March.
- 7.16. In case of any accident, details of the same shall be submitted on Form-II to Gujarat Pollution Control Board.
- 7.17. As per "Public Liability Insurance Act-91" company shall get Insurance Policy, if applicable.
- 7.18. Empty drums and containers of toxic and hazard material shall be treated as per guideline published for "Management & Handling of discarded containers". Records of the same shall be maintained and forwarded to Gujarat Pollution Control Board regularly.
- 7.19. In case of transport of hazardous wastes to a facility for (i.e. treatment, storage and disposal) existing in a State other than the State where hazardous wastes are generated, the occupier shall obtain 'No Objection Certificate' from the State Pollution Control Board or Committee of the concerned State of Union Territory Administration where the facility exists.
- 7.20. Unit shall take all concrete measures to show tangible results in waste generation, reduction, avoidance, reuse and recycle. Actions taken in this regard shall be submitted within three months and also along with Form-4.
- 7.21. Industry shall have to display the relevant information with regards to hazardous waste as indicated in the Hon. Supreme Court's Order in W.P. No.657 of 1995 dated 14<sup>th</sup> October, 2003.
- 7.22. Industry shall have to display on-line data outside the main factory gate with regard to quantity and nature of hazardous chemicals being handled in the plant, including wastewater and air emissions and solid hazardous wastes generated within the factory premises.

## 8. GENERAL CONDITIONS: -

- 8.1. Any change in personnel, equipment or working conditions as mentioned in the consents form/order should immediately be intimated to this Board.
- 8.2. Applicant shall also comply with the general conditions given in annexure I.
- 8.3. Whenever due to accident or other unforeseen act or event, such emissions occur or is apprehended to occur in excess of standards laid down such information shall be forthwith reported to Board, concerned Police Station, Office of Directorate of Health Service, Department of Explosives, Inspectorate of Factories and local body.
- 8.4. In case of failure of pollution control equipments, the production process connected to it shall be stopped. Remedial actions/measures shall be implemented immediately to bring entire situation normal.
- 8.5. The Environmental Management Unit/Cell shall be setup to ensure implementation on and monitoring of environmental safeguards and other conditions stipulated by statutory authorities. The Environmental Management Cell/Unit shall directly report to the Chief Executive of the organization and shall work as a focal point for internalizing environmental issues. These cells/units also coordinate the exercise of environmental audit and preparation of environmental statements.
- 8.6. The Environmental audit shall be carried out yearly and the environmental statements pertaining to the previous year shall be submitting to this State Board latest by 30th September every year.
- 8.7. The Board reserves the right to review and/or revoke the consent and/or make variations in the conditions, which the Board deems, fit in accordance with Section 27 of the Act.
- 8.8. In case of change of ownership, management the name and address of the new owners/ partners/directors proprietor should immediately be intimated to the Board.
- 8.9. Industry shall have to display the relevant information with regard to hazardous waste as indicated in the Hon. Supreme order in w.p. no. 657 of 1995 dated 14<sup>th</sup> October 2003.

 Page 7 of 8

M/s. Aarya processors (Old Name:- Sheetal Nath Silk Mill).(ID\_26808)


*Clean Gujarat Green Gujarat*

ISO - 9001 - 2008 & ISO - 14001 - 2004 Certified Organisation

**9. SPECIFIC CONDITIONS:-**

- 9.1. The authorized actual user of hazardous and other wastes shall maintain records of hazardous and other wastes purchased in a passbook issued by the State Pollution Control Board along with the authorization.
- 9.2. Handling over of the hazardous and other wastes to the authorized actual user shall be only after making the entry in the passbook of the actual user.
- 9.3. In case of renewal of authorization, a self-certified compliance report in respect of effluent, emission standards and the conditions specified in the authorization for hazardous and other wastes shall be submitted to SPCB.
- 9.4. The occupier of the facility shall comply Standard operating procedure/guidelines published by MOEF&CC or CPCB or GPCB from time to time.
- 9.5. Unit shall comply provisions of E-Waste Management Rules-2016.
- 9.6. The disposal of Hazardous Waste shall be carried out as per the waste Management hierarchy.
- 9.7. The occupiers of facilities shall not store the hazardous and other wastes for a period not exceeding **ninety days**. Prior permission of the Board shall be obtained for extension of the storage period.
- 9.8. The occupier shall maintain the records of generation, sale, storage, transport, recycling, co-processing and disposal of hazardous waste and make available during the inspection.
- 9.9. The transportation of the hazardous waste shall be carried out in GPS mounted dedicated vehicles.

**For and on behalf of  
Gujarat Pollution Control Board**

  
(Smt S. V. Bhargava)  
Unit Head, Surat

**NO: GPCB/CCA-SRT-1274/ID-26808/**

**Date:-**

**Issued to:**

**M/s. Aarya processors (Old Name:- Sheetal Nath Silk Mill)**

**Block No: 279, N.H.No. 8,**

**Baleshwar-394315,**

**Tal: Palsana, Dist: Surat.**

Outward No: 597385, 09/08/2021

**M/s. Aarya processors (Old Name:- Sheetal Nath Silk Mill).(ID\_26808)**

# Annexure - B

## Gujarat Pollution Control Board, Regional Office, Surat

### Inspection Report

<b>Name &amp; Address of Unit</b>	Aarya Processors, (GPCB ID- 26808), Block no: 279, N.H. No. 8, Baleshwar, Palsana, Surat.
<b>Reference:</b>	Hon'ble National Green Tribunal, WZB, Pune vide order dated 02-01-2024 passed in Letter complaint dated 13-12-2023 (LP. No. 74/2023, registered as O. A. No. 05/2024) & NHRC Case No. 1255/6/23/2023.
<b>Date and Time of Visit:</b>	01/02/2024, 15:50 PM.
<b>Visited By:</b>	Dr. J. D. Oza (SES – Regional officer), C.C. Haida (SSA)
<b>Contacted Person:</b>	Manvendra Mishra – G.M. of Rajni Prints Pvt. Ltd.
<b>Observations:</b> <ul style="list-style-type: none"><li>• This unit is inspected with reference to Hon'ble National Green Tribunal, WZB, Pune vide order dated 02-01-2024 passed in Letter complaint dated 13-12-2023 (LP. No. 74/2023, registered as O. A. No. 05/2024) of Azad Hind Mazdoor Sena against Aarya Processors.</li><li>• Unit is having CC&amp;A (AWH-114037) for the production of Dying of Art silk Cloth – 1, 25,000 Meter/day., which is valid up to 31-03-2026.</li><li>• During visit production plant is observed in operation and production of Dying of Art silk Cloth is going on.</li><li>• Source of water supply is from own Bore well.</li><li>• Generated industrial w/w is partly reused in drum washing &amp; scrubbers, while remaining is collected in collection cum settling tank &amp; after passing through bar screen, it is discharged in to CETP -GETPL for further treatment &amp; disposal. Unit is member of CETP-GETPL. During visit one waste water sample is collected from final outlet of industry, details are as per data sheet. Flow meter provided at outlet discharge line and reading noted as: Totalizer- 281257.48 M3. During visit no any w/w discharged is outside of the premises.</li><li>• Domestic waste water disposed in to soak pit system/septic tank system.</li><li>• Unit has provided steam Boiler (capacity 6 TPH) and TFH (capacity 1500 U) attached with common stack. Unit has provided MCS, Bag filter followed by alkali water scrubber as APCM with Boiler and MCS, Bag filter followed by alkali water scrubber as APCM with TFH. Imported coal is used as a fuel (Copy attached herewith) with mechanized auto fuel feeding system. During visit Boiler, TFH and provided all APCMs are found in operation. One flue gas stack sample is collected from common stack attached to boiler and TFH; details are as per data sheet. CEMS provided at stack for PM is recorded as: PM – 29.0 kg/hr. Unit has provided D. G. Set of 380 KVA as standby.</li><li>• During visit ETP sludge: @ 150 Kg &amp; Discarded containers: 25 Nos are observed in storage area.</li><li>• @ 30 MT Imported Coal found stored in boiler area.</li></ul>	

- During inspection ambient air quality is observed normal within premises as well as surrounding area.

About complaint details	Status during visit
<p>Perused the report of learned Registrar dated 02.01.2024 on a complaint dated 13.12.2023 made by Azad Hind Mazdoor Sena, A.K. Road, Fulpada, Surat, alleging therein that the respondent- Aarya Processors Pvt. Ltd., Situated at Block No. 279, Baleshwar, Palsana, Gujarat is releasing untreated waste water directly in open drain and is also emitting black polluted smoke in open air because of the use of restricted burn wood, wooden, coal, chindhi, waste fabrics, plastic material, silk cloth, etc. for burning in the mill boiler, leading to huge pollution, resulting in health hazard to the local residents.</p>	<p>* Generated industrial w/w is partly reused in drum washing &amp; scrubbers, while remaining is collected in collection cum settling tank &amp; after passing through bar screen, it is discharged in to CETP -GETPL for further treatment &amp; disposal. During visit no any w/w discharged is outside of the premises.</p> <p>* Imported coal is used as a fuel (Copy attached herewith) with mechanized auto fuel feeding system. One flue gas stack sample is collected from common stack attached to boiler and TFH. During inspection ambient air quality is observed normal within premises as well as surrounding area.</p>



-sd-	-sd-
C. C. Hadia	Dr. J. D. Oza
SSA	Regional officer

# Annexure - C

## ANALYSIS REPORT FOR AIR TYPE : Stack-Flue Gas

Gujarat Pollution Control Board  
Surat  
Plot No. 11-12/2,3  
GIDC - Pandesara  
Surat - 394221  
Tele:(0261) 2442696

Sample ID:416890 - Analysis Completion:06/02/2024

Yarn / Textile processing involving any effluent/emission generating processes including bleaching, dyeing, printing and colouring / LAB  
Inward : 50047

1. Name & : Aarya Processors (Formerly:Sheetal Nath Silk Mill) - 26808
2. Address of the Unit : Block No. 279,N.H. No.-8,  
Baleshwar - 394315,Taluka : Palsana, District : Surat, GIDC : Not In Gidc
3. Nature of Sample : REP-Representative/Grab , (Insp Type : ROU-Routine Visit)
4. Sample Collected By : J.D.OZA, Lab Head
5. Date & Time of Collection & Receipt : 01/02/2024, (1230 to 1300)
6. Date of Start & Completion of Analysis : 02/02/2024 & 06/02/2024
7. Sampling Point : From common stack attached to Boiler & TFH through APCM ~
8. Fuel : Imported coal
9. APCM : MCS+B.F+Alkali Scrubber separately for each
10. Thimble & Weight (gm) : 16/7073
11. Temperature on Collection : 29-Ambient & Volume-Absord Media : 50 ml for SO<sub>2</sub> & 25 ml for NO<sub>x</sub>
12. Volume-Gas Passed : PM: 516 lit., SO<sub>2</sub>: 58.8 lit. & NO<sub>x</sub> : 1525 ml
13. Parameters : 3 & Oper Time(Min) : 30 minutes

Sr	Parameter	Unit	Test Method	Range of Testing	Result
1	PM-Stack	MG/NM3	IS: 11255 (Part – 1), 1985 (Reaffirmed 1999)	1 – 5000 mg/NM3	143
2	SO <sub>2</sub> -Stack (PPM)	PPM	IS: 11255 (Part – 2), 1985 (Reaffirmed 2009)	5 – 500 mg/NM3	4.24
3	NO <sub>x</sub> -Stack	PPM	IS:11255(Part-7), 2005	5 – 500 mg/NM3	2.14

**Laboratory Remarks** : Freeze By:445-lab\_445 Dt.: 06/02/2024

  
J.D.OZA, Lab Head

Field Observation :



ANALYSIS REPORT FOR  
WATER / WASTE WATER SAMPLE **21**

Gujarat Pollution Control Board, Surat  
Plot No. 11-12/2,3  
GIDC - Pandesara  
Surat - 394221  
Tele:(0261) 2442696

Sample ID:416889 - Analysis Completion:06/02/2024

Yarn / Textile processing involving any effluent/emission generating processes including bleaching, dyeing, printing and colouring / LAB  
Inward : 50031

TEST REPORT

Test Report No. : 50031

Date: 06/02/2024

1. Name of the Customer : Aarya Processors (Formerly:Sheetal Nath Silk Mill) - 26808
2. Address : Block No. 279,N.H. No.-8,  
Baleshwar-394315, Taluka : Palsana, District : Surat, GIDC : Not In Gide
3. Nature of Sample : REP-Representative/Grab, (Insp Type : ROU-Routine Visit)
4. Sample Collected By : J.D.OZA, Lab Head
5. Quantity of Sample Received : @5 lit
6. Code No. of the Sample : 416889
7. Date & Time of Collection & Inwarding : 01/02/2024 , (1215 to 1215) & 02/02/2024
8. Date of Start & Completion of Analysis : 02/02/2024 & 06/02/2024
9. Sampling Point : From Final outlet of Industry ~
10. Flow Details (Remarks) : Yes
11. Mode of Disposal : Into CETP-GETPL through u/g pipeline
12. Ultimate Receiving Body : CETP OF GETPL
13. Temperature on Collection : 33 & pH Range on pH Strip :@ 7 to 8 on pH strip
14. Carboys Nos for : Barcode & Color & Appearance :Brownish
15. Water Consumption & W.W.G (KLPD) : Ind :1200.000 , Dom :20.000 & Ind :1000.000 , Dom :20.000

Sr	Parameter	Unit	Test Method	Range of Testing	Result
1	Temperature	Centigrade	IS: 3025 (Part – 9) – 1984(Reaffirmed 2006)	Ambient oC - 60 oC	33
2	pH	pH Units	4500 H+ B APHA Standard Methods 23rd edi.2017	1 – 14 pH value As or	6.40
3	Colour	Pt.Co.Sc.	2120 B APHA Standard Methods 23rd edi. 2017	2 - to 99 Hazen & 1-50	30
4	Total Dissolved Solids	mg/l	Gravimetric method. (2540 C APHA Standard Method	10 – 200000 mg/L	2080
5	Suspended Solids	mg/l	Gravimetric method. (2540 D APHA Standard Method	2 – 10000 mg/L	132
6	Chloride	mg/l	Argentometric method. (4500 Cl <sup>-</sup> B APHA Standard M	1 - 50000 mg/l	590
7	Sulphate	mg/l	APHA(23rd edi) 4500 SO <sub>4</sub> E	2-40mg/l	334
8	Chemical Oxygen Demand	mg/l	APHA (23rd Edition)- 5220 B Open Reflux Method-2C	5.0- 50000 mg/l	985
9	Oil & Grease	mg/l	Liquid – Liquid Partition Gravimetric method. (5520 B	01 – 1000 mg/l	7.2
10	Phenolic Compounds	mg/l	4 Amino Antipyrine method without Chloroform Extra	0.1 – 50 mg/l	0.49
11	B.O.D (3 Days 27oC)	mg/l	3 – Day BOD test. (IS 3025 (Part 44) 1993 Reaffirme	05–50000 mg/l	285

**Laboratory Remarks** : Freeze By:445-lab\_445 Dt.: 06/02/2024

  
J.D.OZA, Lab Head

**Field Observation** :

Note : 1. \* - These parameters are NOT covered under the scope of NABL.

2. The results refer only to the tested samples and applicable parameters. Endorsement of products is neither inferred nor implied.
3. Samples will be destroyed after 10 days from the date of issue of test report unless otherwise specified.
4. This report is not to be reproduced wholly or in part or used in any advertising media without the permission of the Board in writing.
5. The Board is not responsible for the authenticity for the samples not collected by the Board's officials.
6. Total liability of our laboratory is limited to the invoiced amount. Any dispute arising out of this report is subject to Gujarat Jurisdiction only.
7. Permissible Limits: as per Schedule VI of EPA Rules, 1986 as ammended by Second and Third ammendment 1993 for Effluents
8. Physicochemical and microbiological parameters, Std.Methods for Water and Waste Water- 23rd Edition by APHA.
9. Bioassay test (for toxicity) -IS:6582:Part-2:2001; Reaffirmed 2007.



सत्यमेव जयते

# The Gujarat Government Gazette

EXTRAORDINARY  
PUBLISHED BY AUTHORITY

Vol. LVIII ]

FRIDAY, OCTOBER 27, 2017/KARTIKA 5, 1939

Separate paging is given to this Part in order that it may be filed as a Separate Compilation.

## PART IV-C

Statutory Rules and Orders (Other than those published in Parts I, I-A and I-L) made by Statutory Authorities other than the Government of Gujarat including those made by the Government of India, the High Courts, the Director of Municipalities, the Commissioner of Police, the Director of Prohibition and Excise, the District Magistrates and the Election Commission, Election Tribunals, Returning Officers and other authorities under the Election Commission.

THE GUJARAT GOVERNMENT GAZETTE  
EXTRAORDINARY  
PUBLISHED BY AUTHORITY

THURSDAY, OCTOBER 26, 2017

## PART IV-C

GUJARAT POLLUTION CONTROL BOARD  
NOTIFICATION  
SECTOR -10A, NEAR AIR FORCE STATION,  
GANDHINAGAR.

The Gujarat Pollution Control Board in exercise of the powers conferred under clause (d) of Section (2) of the Air (Prevention and Control of Pollution) Act 1981, here by notifies the following fuels as the "APPROVED FUELS" in the state.

- (1) List of "APPROVED FUELS"
1. Coal
  2. Lignite
  3. Furnace Oil/LDO/LSHS
  4. Motor Gasoline
  5. Diesel
  6. Liquid Petroleum Gas (LPG)
  7. Compressed Natural Gas(CNG)/LNG
  8. Kerosene
  9. Naphtha
  10. Firewood
  11. Bio-gas

12. Agro waste/bio fuel/briquettes
13. RDF, as per provisions of Solid Waste Management Rules-2016.
14. Petcoke
15. Charcoal

(2) Petcoke is hereby notified as "APPROVED FUELS" subject to the following conditions:-

- a) The Sulphur content shall not be more than 7 % in any case/circumstance.
- b) Petcoke shall be permitted in the following projects only:-
  - i. Cement manufacturing in kilns
  - ii. Thermal Power Plant/Captive Power Plant of capacity above 25 MW  
(with a condition to mix lime granules in required quantity with Petcoke)
  - iii. Glass manufacturing- up to 25 % of total fuel consumption
  - iv. Refractories manufacturing

(3) For utilization of the above approved fuels, adequate APCM shall be provided by the unit.

(4) CTE/CCA/EC, as the case may be, shall have to be obtained for utilization of these fuels.

(5) The use of Petcoke shall not be permitted in Eco-Sensitive Zone.

**K.C.MISTRY,  
MEMBER SECRETARY,  
GUJARAT POLLUTION CONTROL BOARD  
GANDHINAGAR**



सत्यमेव जयते

# The Gujarat Government Gazette

**EXTRAORDINARY**  
**PUBLISHED BY AUTHORITY**

Vol. LX | FRIDAY, NOVEMBER 13, 2019 / AGRAHAYANA 22, 1941

Separate paging is given to this Part in order that it may be filed as a Separate Compilation.

## PART IV-C

**Statutory Rules and Orders (Other than those published in Parts I, I-A and I-L) made by Statutory Authorities other than the Government of Gujarat including those made by the Government of India, the High Courts, the Director of Municipalities, the Commissioner of Police, the Director of Prohibition and Excise, the District Magistrates and the Election Commission, Election Tribunals, Returning Officers and other authorities under the Election Commission.**

### GUJARAT POLLUTION CONTROL BOARD

#### NOTIFICATION

Gandhinagar, 12<sup>th</sup> December, 2019.

**No: GPCB/P-1/218(A)/530582:** The Gujarat Pollution Control Board in exercise of the powers conferred under clause (d) of Section (2) of the Air (Prevention and Control of Pollution) Act 1981, hereby makes the following amendments in the Gujarat Government Gazette notification in Vol. LVIII on Friday October 27, 2017 and Vol. LIX, Tuesday February 6, 2018.

- (A) In the serial no. (1) of (3) list of approved fuels, "Furnace oil (FO)" is deleted for new Project/Permission.
- (B) The serial no. (2) of notification dated 27.10.2017 and serial no. (B) of notification dated 06.02.2018 shall be replaced and read as under for new Project/Permission:
- (1) Petcoke is hereby notified as "APPROVED FUEL" subject to the following conditions:-
- The Sulphur content shall not be more than 7% in any case/ circumstance.
  - Petcoke shall be permitted in the following projects only:-
    - Cement manufacturing in kilns.
    - Glass manufacturing- up to 25 % of total fuel consumption.
- (C) The new project in the sector mentioned above in serial number (1)(b), using Petcoke or Furnace Oil (FO) as a fuel shall not be permitted in Non-attainment cities declared by the Central Pollution Control Board, New Delhi.

**N. M. TABHANI,**  
Member Secretary,  
Gujarat Pollution Control Board,  
Gandhinagar.

-----  
GOVERNMENT CENTRAL PRESS, GANDHINAGAR