

**ACTION TAKEN REPORT (ATR) OF GUJARAT POLLUTION CONTROL BOARD
IN COMPLIANCE OF HON'BLE NGT WESTERN ZONE BENCH, PUNE IN THE
MATTER OF ORIGINAL APPLICATION NO. 219 OF 2023 (WZ) W.R.T. LETTER
PETITION NO. 70 OF 2023 (COMPLAINT DATED 04.12.2023)**

(I) PREAMBLE

Hon'ble the National Green Tribunal, Western Zone Bench, At Pune Vide Original Application No. 219 OF 2023 (WZ) took cognizance of Complaint dated 04.12.2023 made by the General Secretary, Mr. Padmacharan, r/o A.K. Road, Surat, alleging that Samriddhi Processors Mill, 499, Laxmi Nagar, Udhana, Surat is releasing untreated wastewater into open drain and also using restricted burn wood, wooden coal, chindhi, waste fabric, plastic material, silk cloth, etc. in mill boiler, which is, in turn, emitting huge smoke in open air, causing huge pollution resulting into illness to the local residents and workers of the said industry as well.

Hon'ble NGT issued the following Direction as per order 11/12/2023

Relevant Para 2, is reproduced as “Considering the facts stated in the complaint, we deem it appropriate to call for a report from the Member Secretary, Gujarat Pollution Control Board (GPCB) as to the truthfulness of the contents of the aforesaid complaint and the action taken at their end, if any, within four weeks.”

(II) BASIC INFORMATION OF INDUSTRY

- M/s. Samriddhi Processors (India) Pvt. Ltd is a textile industry which engaged in Dyeing & Printing activity of Grey Cloth at Plot No. 499, 500, GIDC Pandesara – 394 221, Ta – Surat City, Dist- Surat.
- Unit having Consent to Operate/Consolidate Consent and Authorisation (CTO/CC&A) of the Board, which is valid up to date: 30/09/2024 for the manufacturing of “Dyeing and Printing of Grey Cloth” having total production quantity: 85,000 Meters/Day. [Copy of CTO/CC&A is annexed herewith and marked as “Annexure – A”]

(III) THE INSPECTION OF ABOVE MENTION UNIT WAS CARRIED OUT BY THE REGIONAL OFFICE, SURAT OF GUJARAT POLLUTION CONTROL BOARD AND AS PER THE INSPECTION REPORT DATED: 03/02/2024 OBSERVATION/ FACTUAL DETAILS ARE AS UNDER:

- During visit production plant is observed in operation and production of Dying & Printing of Gray Cloth is going on. Source of water supply is from SMC. Generated wastewater is discharge in to CETP-PIL, Pandesara after primary treatment through u/g drainage system for further treatment & disposal. Unit is member of CETP-PIL with booked load of 700 KL/day. During visit one waste water sample is collected from final outlet of industry, details are as per data sheet. During visit no any w/w discharged is outside of the premises. Domestic waste water disposed in to soak pit system/septic tank system.
- Unit has provided steam Boiler (capacity 8 TPH) and TFH (capacity 2000 U) attached with common stack. Unit has provided MCS, Bag filter followed by alkali water scrubber as APCM with Boiler and MCS, Bag filter followed by alkali water scrubber as APCM with TFH. Imported coal is used as a fuel (Copy attached herewith) with mechanized auto fuel feeding system. During visit Boiler, TFH and provided all APCMs are found in operation. One flue gas stack sample is collected from common stack attached to boiler and TFH; details are as per data sheet. Reading of the separate sub energy meter provided for APCM is noted as: 62044 KWH as boiler & 97841 KWH as TFH. CEMS provided at stack for PM is recorded as: PM – 52.02 mg/Nm³. Unit has provided one DG sets (cap. 500 KVA each) as a standby facility.
- During visit ETP sludge: @3-4 MT is observed in storage area. @150 MT Imported Coal found stored in boiler area.
- During inspection ambient air quality is observed normal within premises as well as surrounding area.

[Copy of Inspection Report is annexed herewith and marked as “Annexure – B”]

ANALYSIS RESULTS OF COLLECTED SAMPLES

<u>Final outlet of industry</u>		
<u>Parameters</u>	<u>Results</u>	<u>Norms</u>
pH	7.22	6.5 to 8.5
Colour	20	100
Total Dissolved Solids (TDS)	1886	2100
Suspended Solids (SS)	94	300
Chloride	546	600
Chemical Oxygen Demand (COD)	283	1000
Biological Oxygen Demand (BOD)	84	400
****All the parameters in mg/L except pH and Colour		

<u>Common Stack attached to Boiler & TFH (Thermic Fluid Heater) through APCM</u>		
<u>Parameters</u>	<u>Results</u>	<u>Norms</u>
PM (Particulate Matter)	122 mg/NM ³	150 mg/NM ³
SO ₂	8.76 PPM	100 PPM
NO _x	5.74 PPM	50 PPM

[Copy of Analysis Reports are annexed herewith and marked as “Annexure – C”]

(IV) ACTION TAKEN BY THE BOARD:

Based on Inspection Report Show Cause Notice (SCN) Issued to the unit for below mention non-compliance:

- (i) Unit has installed steam boiler (8 TPH) replacing 6 TPH steam boiler without obtaining prior CTE and CCA of the Board.

[Copy of SCN is annexed herewith and marked as “Annexure – D”]

CONCLUSION:

Looking at the representations of the complainer and inspection report as well as collected samples analysis reports, no violation/non-compliance observed as per the content of the complainer and unit is found in compliance of CCA issued by this Board.

The Board has published Gazetted Notifications for the use of solid fuels in industrial utilities, and the fire wood was included in the list of approved fuels. The copy of Gazetted Notification published by the Board are annexed herewith and marked as “Annexure – E”.

“We regret for not submit action taken report in time”



GUJARAT POLLUTION CONTROL BOARD

PARYAVARAN BHAVAN

Sector-10-A, Gandhinagar 382 010

Phone : (079) 23222425

(079) 23232152

Fax : (079) 23232156

Website : www.gpcb.gov.in

By R.P.A.D

In exercise of the power conferred under section-25 of the Water (Prevention and Control of Pollution) Act-1974, under section-21 of the Air (Prevention and Control of Pollution)-1981 and Authorization under rule 6(2) of the Hazardous And Other Waste (Management and Transboundary) Rules, 2016 framed under the Environmental (Protection) Act-1986. This Board is empowered to Grant CC&A.

And whereas Board has received consolidated consent application letter no. 165418 dated 19-11-2019 for the Consolidated Consent and Authorization (CC & A) of this Board under the provisions / rules of the aforesaid Acts. Consents & Authorization are hereby granted as under:

CONSENTS AND AUTHORISATION:

(Under the provisions /rules of the aforesaid environmental acts)

To,
M/s. Samridhi Processors (India) Pvt. Ltd.
Plot No: 499, 500,
GIDC, Pandesara-394221,
Tal: Surat City, Dist: Surat.

1. Consent Order No. AWH-105945 Date of issue: 30-12-2019.
2. The consents shall be valid upto 30-09-2024 for the use of outlet for the discharge of treated effluent and emission due to operation of industrial plant for manufacturing of the following items/ products:

Sr. No.	Product	Quantity
1	Dyeing & Printing of Gray Cloth	85,000 Meter/Day

Subject to specific condition:

1. Industry shall manage Solid Wastes generated from industrial activities as per Solid Waste Management Rules-2016 (solid waste as defined in Rule-3(46)).
 2. As per Provisions of Rule 18 of Solid Waste Management Rules-2016 you are directed to make an arrangement in Utilities to replace at least five percent (5%) of your solid fuel requirement by 'refused derived fuel'.
 3. Industry shall provide dedicated storage facility for fly ash.
 4. Industry shall comply with fly ash notification 1999 as amended from time to time.
3. CONDITIONS UNDER THE WATER ACT:

- 3.1. Source of Water:- SMC Water Supply.
- 3.2. The quantity of the fresh water consumption for industrial purpose shall not exceed 835 KL/Day.
- 3.3. The quantity of the fresh water consumption for domestic purpose shall not exceed 15 KL/Day.

Page 1 of 8

M/s. Samridhi Processors (India) Pvt. Ltd. (ID-20106)

Clean Gujarat Green Gujarat
ISO-9001-2008 & ISO-14001 - 2004 Certified Organisation

Outward No: 5509/2019

- 3.4. The quantity of the industrial effluent to be generated from the manufacturing process and other ancillary industrial operations shall not exceed 700 KL/Day (Total Booked load in CETP: 700 KL/Day)
- 3.5. The quantity of domestic waste water shall not exceed 15 KL/Day.
- 3.6. Domestic effluent shall be disposed off through septic tank/soak pit system.
- 3.7. The applicant shall operate effluent treatment system efficiently so that effluent from the industrial unit shall conform to the CETP inlet norms mentioned below however the final discharge of treated effluent from CETP shall adhere to the prescribed standards for CETP of M/s. Pandesara Infrastructure Ltd(PIL).

PARAMETERS	CETP INLET NORMS
PH	6.5 TO 8.5
Temperature	40° C
Colour (pt.co.scale) in units	100 units
Suspended Solids	300 mg/l
Oil and Grease	10 mg/l
Chlorides	600 mg/l
Phenolic Compounds	1 mg/l
Sulphides	2 mg/l
Ammonical Nitrogen	50 mg/l
Total Chromium	2 mg/l
Hexavalent Chromium	0.1 mg/l
BOD (5 days at 20°C)	400 mg/l
COD	1000 mg/l
Total Dissolved Solids	2100 mg/l

- 3.8. The final treated effluent conforming to the above standards shall be fully conveyed into CETP of M/s. Pandesara Infrastructure Ltd(PIL). through underground drainage system of PIL & in no case effluent shall be discharged in to Environment by any means.
- 3.9. In case of failure of CETP, applicant shall have to treat the trade effluent of their unit fully so as to achieve the quality of the treated effluent from their industrial premises as per the GPCB norms mentioned below:-

PARAMETERS	GPCB NORMS
PH	6.5 TO 8.5
Temperature	40° C
Suspended Solids	100 mg/l
Oil and Grease	10 mg/l
Total Dissolved Solids	2100 mg/l
Phenolic Compounds	1 mg/l
Sulphides	2.0 mg/l
Ammonical Nitrogen	50 mg/l
Total Chromium	2 mg/l
Hexavalent Chromium	0.1 mg/l
BOD (5 days at 20°C)	30 mg/l
COD	100 mg/l



GUJARAT POLLUTION CONTROL BOARD

PARYAVARAN BHAVAN

Sector-10-A, Gandhinagar 382 010

Phone : (079) 23222425

(079) 23232152

Fax : (079) 23232156

Website : www.gpcb.gov.in

Chlorides	600 mg/l
Sulphate	1000 mg/l

OR

The applicant shall stop or production activities if the effluent is not adequately treated by the CETP of PIL to conform to the standards specified by G.P.C.B.

- 3.10. The applicant shall be responsible for conveyance of entire treated effluent to the CETP of M/s. PIL & due care shall be taken to avoid any leakage or spillage of effluent during conveyance of treated effluent through drain.
- 3.11. Unit shall provide flow meters at inlet & outlet of ETP & maintain its record.
- 3.12. The applicant shall inform renewal/termination of CETP membership well in advance to GPCB.
- 3.13. The applicant shall be required to make storage facilities to store the primary treated effluent for at least 48 hours by providing acid proof brick lined impervious tanks/HDPE tanks.
- 3.14. The applicant shall make fixed arrangement for loading the effluent after primary treatment to the CETP. The unit shall not keep any by-pass line or system or loose or flexible pipe line for discharging effluent into the under ground drainage system of PIL.
- 3.15. Leachate from the hazardous solid waste, if any shall also be connected into a collection tank through leachate collection facilities and shall be conveyed alongwith industrial effluent to the CETP of PIL.
- 3.16. Magnetic flow meters shall be installed at the inlet & outlet of effluent collection tanks/ETP to measure the quantity of effluent discharging in to underground drainage system of PIL.
- 3.17. The ENTIRE quantity of industrial effluent shall have to be conveyed by PIL. In no circumstances the effluent either treated or untreated shall be discharged any where else.
- 3.18. Disposal system for storm water shall be provided separately. In no circumstances storm water shall be mixed with the industrial effluent.
- 3.19. PIL member unit have to modify / improve performance of existing Effluent treatment facilities for efficiency & adequacy in order to comply with prescribed in let standards.
- 3.20. The applicant shall keep accurate records of quantity of production of each product, quantity of water consumption, quantity of effluent generated and consumption of electricity on day to day basis and required to submit the complied record of one month to GPCB & PIL on or before fifth day of the succeeding month.
- 3.21. In case of shut-down of plant for more than three days for any reason, the PIL unit member shall intimate to PIL authority & GPCB well in advance for the better operation & management of CETP.
- 3.22. The authorized representative of PIL may have right of entry at any time for the purpose of inspection and monitoring the effluent collection facilities/ETP (if required) of the applicant.
- 3.23. If the PIL authority terminates the membership of the applicant for CETP, the PIL member unit shall have to close down the manufacturing activities/industrial operation of the process plant immediately until the PIL membership is resumed.
- 3.24. The applicant shall put up at the entrance a board displaying PIL membership number & date of joining of PIL, the name of unit, particulars of the products/ process and the name of proprietor/partners /directors of the unit and the electricity consumer number as on the record of GSECL.

4. CONDITIONS UNDER THE AIR ACT:

4.1. The following shall be used as a fuel in Steam Boiler, Thermo Pack, and D.G.Sets respectively.

Sr. No.	Utility	Fuel	Quantity
1)	Steam Boiler (6 TPH)	Coal	18 MT/Day
2)	Thermopack (2000 U)		
3)	D.G.Set (500 KVA)	Diesel	30 lit/Hr

4.2. The applicant shall install & operate comprehensive adequate air pollution control system in order to achieve prescribed norms.

4.3. The flue gas emission through stack attached to Steam Boiler, Thermo Pack, and D.G.Sets shall conform to the following standards:

Stack No.	Stack attached to	Stack height in Meter	Air Pollution Control system	Parameter	Permissible Limit
1	Steam Boiler (6 TPH)	31 (Common Stack)	Multi Cyclone Separator & Bag Filter	Particulate Matter	150 mg/NM ³
	SO ₂			100 ppm	
	Thermopack (2000 U)		Multi Cyclone Separator & Bag Filter	NO _x	50 ppm
2	D.G.Set-1 nos (500 KVA)	11	---	Particulate Matter	150 mg/NM ³
	Stand by			SO ₂	100 ppm
				NO _x	50 ppm

4.4. There shall be no process emission from the manufacturing process as well as any other ancillary process.

4.5. Industry shall take adequate measure to control dusting due to storage, transportation & handling of Coal/Lignite & fly ash.

4.6. Industry shall comply with Coal handling guideline of the Board.

4.7. Industry shall comply with fly ash notification 1999 as amended from time to time.

4.8. The concentration of the following parameters in the ambient air within the premises of the industry and a distance of 10meters from the source) other than the stack/vent) shall not exceed the following levels.

PARAMETERS	PERMISSIBLE LIMIT (Microgram/M ³)	
	Annual	24 Hrs Average
Particulate Matter-10 (PM ₁₀)	60	100
Particulate Matter- 2.5 (PM _{2.5})	40	60
SO ₂	50	80
NO _x	40	80

4.9. The applicant shall provide portholes, ladder, platform etc at chimney(s) for monitoring the air emissions and the same shall be open for inspection to/and for use of Board's staff. The chimney(s) vents attached to various sources of emission shall be designed by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.



GUJARAT POLLUTION CONTROL BOARD

PARYAVARAN BHAVAN

Sector-10-A, Gandhinagar 382 010

Phone : (079) 29222425

(079) 23232152

Fax : (079) 23232156

Website : www.gpcb.gov.in

- 4.10. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standards in respect of noise to less than 75dB(A) during day time and 70 dB (A) during night time. Daytime is reckoned in between 6a.m. and 10 p.m. and nighttime is reckoned between 10 p.m. and 6 a.m.

5. D.G. SETS CONDITIONS

The D.G. Set shall have acoustic enclosure and shall comply with the standards specified at Sr. no. 95 of Schedule-I of the rule-3 of E.P. Rules -1986 and Noise pollution level as per the Air Act-1981.

D.G. Sets standards:-

The flue gas emission through stack attached to D.G. Sets shall conform to the following standards.

- The minimum height of stack to be provided with each of the generator set shall be $H=h + 0.2 (KVA)^{1/2}$, where H= Total stack height in meter, h= height of the building in meters where or by the side of which the generator set is installed.
- Noise from DG set shall be controlled by providing an acoustic enclosure or by treating the room acoustically, at the users end.
- The acoustic enclosure or acoustic treatment of the room shall be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on the higher side (if the actual ambient noise is on the higher side, it may not be possible to check the performance of the acoustic enclosure/ acoustic treatment. Under such circumstances the performance may be checked for noise reduction up to actual ambient noise level, preferably, in the night time). The measurement for insertion loss may be done at different points at 0.5 m from the acoustic enclosure/room, and the averaged.
- The D.G. Set shall be provided with proper exhaust muffler with insertion loss of minimum 25 dB (A).
- All efforts shall be made to bring down the noise level due to the D.G.Set, outside the premises, within the ambient noise requirements by proper siting and control measures.
- Installation of a D.G. Sets must be strictly in compliance with the recommendations of the D.G.Set manufacturer.
- A proper routine and preventive maintenance procedure for the D.G.Set should be set and followed in consultation with the DG Set manufacture which would help prevent noise levels of the DG Set from deteriorating with use.

6. AUTHORIZATION as per HAZARDOUS AND OTHER WASTE (MANAGEMENT AND TRANSBOUNDARY) RULES, 2016 Form-2 [See rule 6 (2)]

Form for grant of authorization for occupier or operator handling Hazardous waste

6.1 Authorization order No:- AWH-105945 date of Issue: 30-12-2019.

6.2 M/s. Samridhi Processors (India) Pvt. Ltd. is hereby granted an authorization to operate facility for following hazardous wastes on the premises situated at Plot No: 499, 500, GIDC, Pandesara-394221, Tal: Surat City, Dist: Surat.

Sr. No.	Waste	Quantity	Schedule-I/ Category	Facility
1	Chemical Sludge from waste water treatment	0.17 MT/Year	35.3	Collection, Storage, Transportation and disposal at GPCB authorized TSDF Site.

2	Used or Spent Oil	0.450 Lit/Year	5.1	Collection, storage, transportation and disposal by selling to Registered re-refiners.
3	Empty barrels/containers/liners contaminated with hazardous chemicals/wastes	6.8 MT/Year	33.1	Collection, storage transportation and disposal to authorized decontaminator

6.3 The authorization shall be valid up to 30-09-2024.

6.4 The authorization is subject to the conditions stated below and such other conditions as may be specified in the rules from time to time under the Environment (Protection) Act-1986.

6.5 The authorization is granted to operate a facility for collection, storage within factory premises transportation and ultimate disposal of Hazardous wastes as per condition no.6.2 to the industry having valid CCA of this Board.

7. TERMS AND CONDITIONS OF AUTHORISATION

7.1. The applicant shall comply with the provisions of the Environment (Protection) Act-1986 and the rules made there under.

7.2. The authorization or its renewal shall be produced for inspection at the request of an officer authorized by the Gujarat Pollution Control Board.

7.3. The persons authorized shall not rent, lend, sell, and transfer or otherwise transport the hazardous wastes without obtaining prior permission of the Gujarat Pollution Control Board.

7.4. Any unauthorized change in personnel, equipment or working conditions as mentioned in the authorization order by the persons authorized shall constitute a breach of this authorization.

7.5. The person authorized shall implement Emergency Response Procedure (ERP) for which this authorization is being granted considering all site specific possible scenarios such as spillages, leakages, fire etc. and their possible impacts and also carry out mock drill in this regard at regular interval of time;

7.6. The person authorized shall comply with the provisions outlined in the Central Pollution Control Board guidelines on "Implementing Liabilities for Environmental Damages due to Handling and Disposal of Hazardous Wastes and Penalty"

7.7. It is the duty of the authorized person to take prior permission of the Gujarat Pollution Control Board to close down the facility.

7.8. An application for the renewal of an authorization shall be made as laid down in rules 6(2) under Hazardous and Other Waste Rules, 2016.

7.9. The imported hazardous and other wastes shall be fully insured for transit as well as for any accidental occurrence and its clean-up operation.

7.10. The record of consumption and fate of the imported hazardous and other wastes shall be maintained.

7.11. The hazardous and other wastes which gets generated during recycling or reuse or recovery or pre-processing or utilization of imported hazardous or other wastes shall be treated and disposed of as per specific conditions of authorization.

7.12. The importer or exporter shall bear the cost of import or export and mitigation of damages if any.



GUJARAT POLLUTION CONTROL BOARD

PARYAVARAN BHAVAN

Sector-10-A, Gandhinagar 382 010

Phone : (079) 23222425

(079) 23232152

Fax : (079) 23232156

Website : www.gpcb.gov.in

- 7.13. Any other conditions for compliance as per the Guidelines issued by the Ministry of Environment, Forest and Climate Change or Central Pollution Control Board from time to time.
- 7.14. The waste generator shall be totally responsible for (i.e. collection, storage, transportation and ultimate disposal) the wastes generated.
- 7.15. Records of waste generation, its management and annual return shall be submitted to Gujarat Pollution Control Board in Form-4 by 30th day of June of every year for the preceding period April to March.
- 7.16. In case of any accident, details of the same shall be submitted on Form-11 to Gujarat Pollution Control Board.
- 7.17. As per "Public Liability Insurance Act-91" company shall get Insurance Policy, if applicable.
- 7.18. Empty drums and containers of toxic and hazard material shall be treated as per guideline published for "Management & Handling of discarded containers". Records of the same shall be maintained and forwarded to Gujarat Pollution Control Board regularly.
- 7.19. In case of transport of hazardous wastes to a facility for (i.e. treatment, storage and disposal) existing in a State other than the State where hazardous wastes are generated, the occupier shall obtain 'No Objection Certificate' from the State Pollution Control Board or Committee of the concerned State of Union Territory Administration where the facility exists.
- 7.20. Unit shall take all concrete measures to show tangible results in waste generation, reduction, avoidance, reuse and recycle. Actions taken in this regard shall be submitted within three months and also along with Form-4.
- 7.21. Industry shall have to display the relevant information with regards to hazardous waste as indicated in the Hon. Supreme Court's Order in W.P. No.657 of 1995 dated 1st October, 2003.
- 7.22. Industry shall have to display on-line data outside the main factory gate with regard to quantity and nature of hazardous chemicals being handled in the plant, including wastewater and air emissions and solid hazardous wastes generated within the factory premises.

8. GENERAL CONDITIONS: -

- 8.1. Any change in personnel, equipment or working conditions as mentioned in the consents form/order should immediately be intimated to this Board.
- 8.2. Applicant shall also comply with the general conditions given in annexure I.
- 8.3. Whenever due to accident or other unforeseen act or ever, such emissions occur or is apprehended to occur in excess of standards laid down such information shall be forthwith reported to Board, concerned Police Station, Office of Directorate of Health Service, Department of Explosives, Inspectorate of Factories and local body.
- 8.4. In case of failure of pollution control equipments, the production process connected to it shall be stopped. Remedial actions/measures shall be implemented immediately to bring entire situation normal.
- 8.5. The Environmental Management Unit/Cell shall be setup to ensure implementation on and monitoring of environmental safeguards and other conditions stipulated by statutory authorities. The Environmental Management Cell/Unit shall directly report to the Chief Executive of the organization and shall work as a focal point for internalizing environmental issues. These cells/units also coordinate the exercise of environmental audit and preparation of environmental statements.
- 8.6. The Environmental audit shall be carried out yearly and the environmental statements pertaining to the previous year shall be submitting to this State Board latest by 30th September every year.

- 8.7. The Board reserves the right to review and/or revoke the consent and/or make variations in the conditions, which the Board deems, fit in accordance with Section 27 of the Act.
- 8.8. In case of change of ownership/management the name and address of the new owners/ partners/directors/proprietor should immediately be intimated to the Board.
- 8.9. Industry shall have to display the relevant information with regard to hazardous waste as indicated in the Hon. Supreme order in w.p. no. 657 of 1995 dated 14th October 2003.

9. SPECIFIC CONDITIONS:-

- 9.1. The authorized actual user of hazardous and other wastes shall maintain records of hazardous and other wastes purchased in a passbook issued by the State Pollution Control Board along with the authorization.
- 9.2. Handling over of the hazardous and other wastes to the authorized actual user shall be only after making the entry in the passbook of the actual user.
- 9.3. In case of renewal of authorization, a self-certified compliance report in respect of effluent, emission standards and the conditions specified in the authorization for hazardous and other wastes shall be submitted to SPCB.
- 9.4. The occupier of the facility shall comply Standard operating procedure/guidelines published by MOEF&CC or CPCB or GPCB from time to time.
- 9.5. Unit shall comply provisions of E-Waste Management Rules-2016.
- 9.6. The disposal of Hazardous Waste shall be carried out as per the waste Management hierarchy.
- 9.7. The occupiers of facilities shall not store the hazardous and other wastes for a period not exceeding ninety days. Prior permission of the Board shall be obtained for extension of the storage period.
- 9.8. The occupier shall maintain the records of generation, sale, storage, transport, recycling, co processing and disposal of hazardous waste and make available during the inspection.
- 9.9. The transportation of the hazardous waste shall be carried out in GPS mounted dedicated vehicles.

For and on behalf of
Gujarat Pollution Control Board

G.B. Vasavada
(G.B. Vasavada)
09/01/2020
Scientific Officer & I/C Unit Head, Surat
Date:-

NO: GPCB/CCA-SRT-702(4)/ID-20106/
Issued to:
M/s. Samriddhi Processors (India) Pvt. Ltd.
Plot No: 499, 500,
GIDC, Pandesara-394221,
Tal: Surat City, Dist: Surat.

Annexure - B

Gujarat Pollution Control Board, Regional Office, Surat

Inspection Report

Name & Address of Unit	Samriddhi Processors (India) Pvt. Ltd., (GPCB ID- 20106), Plot no: 499, 500, GIDC Pandesara, Surat.
Reference:	H. O. mail date: 17-01-2024 regarding, Hon'ble National Green Tribunal, WZB, Pune vide order dated 11-12-2023 passed in Letter complaint dated 04.12.2023 (LP. No. 70/2023, registered as O. A. No. 219/2023) (Copy attached herewith)
Date and Time of Visit:	03/02/2024, 17:30 PM.
Visited By:	Dr. J. D. Oza (SES – Regional officer), C.C. Haida (SSA)
Contacted Person:	Ankit Singhi - Manager of Samriddhi Processors (India) Pvt. Ltd.
Observations: <ul style="list-style-type: none">• This unit is inspected with reference to mail date: 17-01-2024 from unit head, surat regarding Hon'ble National Green Tribunal, WZB, Pune vide order dated 11-12-2023 passed in Letter complaint dated 04-12-2023 (LP. No. 70/2023, registered as O. A. No. 219/2023) of All India Forward Block against Samriddhi Processors (India) Pvt. Ltd.• Unit is having CC&A (AWH-105945) for the production of Dying & Printing of Gray Cloth – 85,000 Meter/day. This is valid up to 30-09-2024.• During visit production plant is observed in operation and production of Dying & Printing of Gray Cloth is going on.• Source of water supply is from SMC.• Generated waste water is discharge in to CETP-PIL, Pandesara after primary treatment through u/g drainage system for further treatment & disposal. Unit is member of CETP-PIL with booked load of 700 KL/day. During visit one waste water sample is collected from final outlet of industry, details are as per data sheet. During visit no any w/w discharged is outside of the premises.• Domestic waste water disposed in to soak pit system/septic tank system.• Unit has provided steam Boiler (capacity 8 TPH) and TFH (capacity 2000 U) attached with common stack. Unit has provided MCS, Bag filter followed by alkali water scrubber as APCM with Boiler and MCS, Bag filter followed by alkali water scrubber as APCM with TFH. Imported coal is used as a fuel (Copy attached herewith) with mechanized auto fuel feeding system. During visit Boiler, TFH and provided all APCMs are found in operation. One flue gas stack sample is collected from common stack attached to boiler and TFH; details are as per data sheet. Reading of the separate sub energy meter provided for APCM is noted as: 62044 KWH as boiler & 97841 KWH as TFH. CEMS provided at stack for PM is recorded as: PM – 52.02 mg/Nm³. Unit has provided one DG sets (cap. 500 KVA each) as a standby facility.• During visit ETP sludge: @ 3-4 MT is observed in storage area.• @ 150MT Imported Coal found stored in boiler area.	

- During inspection ambient air quality is observed normal within premises as well as surrounding area.

About complaint details	Status during visit
<p>Perused the report of learned Registrar dated 07.12.2023 in respect of a complain dated 04.12.2023 made by All India Forward Block through its General Secretary Mr. Padmacharan, r/o A. K. Road, Surat against Samriddhi Processors Mills, 499, Laxmi Nagar, Udhana, Surat, alleging that the respondent- industry is releasing untreated waste water into open drain and also using restricted burn wood, wooden, coal, chindhi, waste fabrics, plastic material, silk cloth, etc. in mill boiler, which is, in turn, emitting huge smoke in open air, causing huge pollution resulting in to illness to the local residents and workers of the said industry as well.</p>	<p>* Generated waste water is discharge in to CETP-PIL, Pandesara after primary treatment through u/g drainage system for further treatment & disposal. During visit no any w/w discharged is outside of the premises. * Imported coal is used as a fuel (Copy attached herewith) with mechanized auto fuel feeding system. One flue gas stack sample is collected from common stack attached to boiler and TFH. During inspection ambient air quality is observed normal within premises as well as surrounding area.</p>

During visit @ 150 MT Imported Coal found stored in boiler area.



-sd-	-sd-
C. C. Hadia	Dr. J. D. Oza
SSA	Regional officer



ANALYSIS REPORT FOR
WATER / WASTE WATER SAMPLE

Annexure - C

Gujarat Pollution Control Board, Surat

Plot No. 11-12/2,3

GIDC - Pandesara

Surat - 394221

Tele:(0261) 2442696

Sample ID:417370 - Analysis Completion:13/02/2024

Yarn / Textile processing involving any effluent/emission generating processes including bleaching, dyeing, printing and colouring / LAB
Inward : 50130

TEST REPORT

Test Report No. : 50130

Date: 13/02/2024

1. Name of the Customer : Samriddhi Pcessos (India) Pvt. Ltd.(Old Name-Govinda Pcessos) - 20106
2. Address : 499, ,GIDC,Pandesaa
Pandessaa-394221, Taluka : Surat City, District : Surat, GIDC : Pandesara
3. Nature of Sample : REP-Representative/Grab, (Insp Type : COM-On Complaint)
4. Sample Collected By : J.D.OZA, Lab Head
5. Quantity of Sample Received : @ 5 Ltr
6. Code No. of the Sample : 417370
7. Date & Time of Collection & Inwarding : 03/02/2024 , (1735 to 1735) & 05/02/2024
8. Date of Start & Completion of Analysis : 05/02/2024 & 13/02/2024
9. Sampling Point : From Final outlet of Industry ~
10. Flow Details (Remarks) : Yes
11. Mode of Disposal : Into CETP-PEPL through u/g pipeline
12. Ultimate Receiving Body : No generation of industrial wastewater
13. Temperature on Collection : 32 & pH Range on pH Strip :@ 7 to 8 on pH strip
14. Carboys Nos for : Barcode & Color & Appearance :Brownish
15. Water Consumption & W.W.G (KLPD) : Ind :835.000 , Dom :15.000 & Ind :700.000 , Dom :15.000

Sr	Parameter	Unit	Test Method	Range of Testing	Result
1	Temperature	Centigrade	IS: 3025 (Part – 9) – 1984(Reaffirmed 2006)	Ambient oC - 60 oC	32
2	pH	pH Units	4500 H+ B APHA Standard Methods 23rd edi.2017	1 – 14 pH value As or	7.22
3	Colour	Pt.Co.Sc.	2120 B APHA Standard Methods 23rd edi. 2017	2 - to 99 Hazen & 1-50	20
4	Total Dissolved Solids	mg/l	Gravimetric method. (2540 C APHA Standard Method	10 – 200000 mg/L	1886
5	Suspended Solids	mg/l	Gravimetric method. (2540 D APHA Standard Method	2 – 10000 mg/L	94
6	Chloride	mg/l	Argentometric method. (4500 Cl ⁻ B APHA Standard M	1 - 50000 mg/l	546
7	Sulphate	mg/l	APHA(23rd edi) 4500 SO ₄ E	2-40mg/l	260
8	Chemical Oxygen Demand	mg/l	APHA (23rd Edition)- 5220 B Open Reflux Method-2C	5.0- 50000 mg/l	283
9	Oil & Grease	mg/l	Liquid – Liquid Partition Gravimetric method. (5520 B	01 – 1000 mg/l	6.4
10	Phenolic Compounds	mg/l	4 Amino Antipyrrene method without Chloroform Extra	0.1 – 50 mg/l	0.23
11	B.O.D (3 Days 27oC)	mg/l	3 – Day BOD test. (IS 3025 (Part 44) 1993 Reaffirme	05–50000 mg/l	84

Laboratory Remarks : Freeze By:445-lab_445 Dt.: 13/02/2024

J.D.OZA, Lab Head

Field Observation :

Note : 1. * - These parameters are NOT covered under the scope of NABL.

- The results refer only to the tested samples and applicable parameters. Endorsement of products is neither inferred nor implied.
- Samples will be destroyed after 10 days from the date of issue of test report unless otherwise specified.
- This report is not to be reproduced wholly or in part or used in any advertising media without the permission of the Board in writing.
- The Board is not responsible for the authenticity for the samples not collected by the Board's officials.
- Total liability of our laboratory is limited to the invoiced amount. Any dispute arising out of this report is subject to Gujarat Jurisdiction only.
- Permissible Limits: as per Schedule VI of EPA Rules, 1986 as ammended by Second and Third ammendment 1993 for Effluents
- Physicochemical and microbiological parameters, Std.Methods for Water and Waste Water- 23rd Edition by APHA.
- Bioassay test (for toxicity) -IS:6582:Part-2:2001; Reaffirmed 2007.

**ANALYSIS REPORT FOR AIR****TYPE : Stack-Flue Gas**

Gujarat Pollution Control Board

Surat

Plot No. 11-12/2,3

GIDC - Pandesara

Surat - 394221

Tele:(0261) 2442696

Sample ID:417371 - Analysis Completion:06/02/2024

Yarn / Textile processing involving any effluent/emission generating processes including bleaching, dyeing, printing and colouring / LAB

Inward : 50144

1. Name & : Samriddhi Pcessos (India) Pvt. Ltd.(Old Name-Govinda Pcessos) - 20106
2. Address of the Unit : 499, ,GIDC,Pandesaa
Pandessaa - 394221,Taluka : Surat City, District : Surat, GIDC : Pandesara
3. Nature of Sample : REP-Representative/Grab , (Insp Type : COM-On Complaint)
4. Sample Collected By : J.D.OZA, Lab Head
5. Date & Time of Collection & Receipt : 03/02/2024, (1750 to 1820)
6. Date of Start & Completion of Analysis : 05/02/2024 & 06/02/2024
7. Sampling Point : From common stack attached to Boiler & TFH through APCM ~
8. Fuel : Imported coal
9. APCM : MCS+B.F+Alkali Scrubber separately for each
10. Thimble & Weight (gm) : 16/4933
11. Temperature on Collection : 33-Ambient & Volume-Absord Media : 50 ml for SO2 & 25 ml for NOx
12. Volume-Gas Passed : PM : 494 lit., SO2 : 57.0 lit. & NOx : 1328 ml
13. Parameters : 3 & Oper Time(Min) : 30 minutes

Sr	Parameter	Unit	Test Method	Range of Testing	Result
1	PM-Stack	MG/NM3	IS: 11255 (Part – 1), 1985 (Reaffirmed 1999)	1 – 5000 mg/NM3	122
2	SO2-Stack (PPM)	PPM	IS: 11255 (Part – 2), 1985 (Reaffirmed 2009)	5 – 500 mg/NM3	8.76
3	NOX-Stack	PPM	IS:11255(Part-7), 2005	5 – 500 mg/NM3	5.74

Laboratory Remarks : Freeze By:445-lab_445 Dt.: 06/02/2024
J.D.OZA, Lab Head

Field Observation :



GUJARAT POLLUTION CONTROL BOARD

PARYAVARAN BHAVAN, SECTOR 10-A,
GANDHINAGAR - 382010,
(T) 079-23232152

R.P.A.D.

Show Cause Notice

WHEREAS you are having an industrial plant namely M/s. Samriddhi Pcessos (India) Pvt. Ltd. (Old Name: Govinda Processors) located at Plot No: 499, Pandesara GIDC, Pandesara - 394221, Tal: Surat City, Dist: Surat.

AND WHEREAS, the Board has granted Consolidated Consent and Authorization, AWH-105945, valid up to 30/09/2024.

AND WHEREAS Show Cause Notice was issued under the Air (Prevention and Control of Pollution) Act, 1981, as amended from time to time on dated: 29/12/2023.

AND WHEREAS, during visit of your industrial plant on 03/02/2024 by the Board Officials, it was observed that:

- Unit has installed Steam Boiler (8 TPH) replacing 6 TPH Steam Boiler without obtaining prior CTE and CCA of the Board.

AND WHEREAS, you have submitted/uploaded certificate for use of Boiler in Form VI from Gujarat Boiler Inspection Department on 16/02/2024 showing Maximum continuous Evaporation 8,000 Kg/hr.

In view of the above, you are called upon to show cause within 7 days why legal action should not be initiated against your industry for contravening the provisions of the Environmental Laws.

For and on behalf of
Gujarat Pollution Control Board,


(Dr. S. N. Agravat)
Unit Head, Surat

NO: GPCB/CCA-SRT-702(4)/ID: 20106/

Date:

Issued to:

M/s. Samriddhi Pcessos (India) Pvt. Ltd. (Old Name: Govinda Processors)

Plot No: 499, Pandesara GIDC,

Pandesara - 394221,

Tal: Surat City, Dist: Surat.



सत्यमेव जयते

The Gujarat Government Gazette
EXTRAORDINARY
PUBLISHED BY AUTHORITY

Vol. LVIII]

FRIDAY, OCTOBER 27, 2017/KARTIKA 5, 1939

Separate paging is given to this Part in order that it may be filed as a Separate Compilation.

PART IV-C

Statutory Rules and Orders (Other than those published in Parts I, I-A and I-L) made by Statutory Authorities other than the Government of Gujarat including those made by the Government of India, the High Courts, the Director of Municipalities, the Commissioner of Police, the Director of Prohibition and Excise, the District Magistrates and the Election Commission, Election Tribunals, Returning Officers and other authorities under the Election Commission.

THE GUJARAT GOVERNMENT GAZETTE
EXTRAORDINARY
PUBLISHED BY AUTHORITY

THURSDAY, OCTOBER 26, 2017

PART IV-C

GUJARAT POLLUTION CONTROL BOARD
NOTIFICATION
SECTOR -10A, NEAR AIR FORCE STATION,
GANDHINAGAR.

The Gujarat Pollution Control Board in exercise of the powers conferred under clause (d) of Section (2) of the Air (Prevention and Control of Pollution) Act 1981, here by notifies the following fuels as the "APPROVED FUELS" in the state.

- (1) List of "APPROVED FUELS"
1. Coal
 2. Lignite
 3. Furnace Oil/LDO/LSHS
 4. Motor Gasoline
 5. Diesel
 6. Liquid Petroleum Gas (LPG)
 7. Compressed Natural Gas(CNG)/LNG
 8. Kerosene
 9. Naphtha
 10. Firewood
 11. Bio-gas

12. Agro waste/bio fuel/briquettes
13. RDF, as per provisions of Solid Waste Management Rules-2016.
14. Petcoke
15. Charcoal

(2) Petcoke is hereby notified as "APPROVED FUELS" subject to the following conditions:-

- a) The Sulphur content shall not be more than 7 % in any case/circumstance.
- b) Petcoke shall be permitted in the following projects only:-
 - i. Cement manufacturing in kilns
 - ii. Thermal Power Plant/Captive Power Plant of capacity above 25 MW
(with a condition to mix lime granules in required quantity with Petcoke)
 - iii. Glass manufacturing- up to 25 % of total fuel consumption
 - iv. Refractories manufacturing

(3) For utilization of the above approved fuels, adequate APCM shall be provided by the unit.

(4) CTE/CCA/EC, as the case may be, shall have to be obtained for utilization of these fuels.

(5) The use of Petcoke shall not be permitted in Eco-Sensitive Zone.

**K.C.MISTRY,
MEMBER SECRETARY,
GUJARAT POLLUTION CONTROL BOARD
GANDHINAGAR**



सत्यमेव जयते

The Gujarat Government Gazette

EXTRAORDINARY
PUBLISHED BY AUTHORITY

Vol. LX | FRIDAY, NOVEMBER 13, 2019 / AGRAHAYANA 22, 1941

Separate paging is given to this Part in order that it may be filed as a Separate Compilation.

PART IV-C

Statutory Rules and Orders (Other than those published in Parts I, I-A and I-L) made by Statutory Authorities other than the Government of Gujarat including those made by the Government of India, the High Courts, the Director of Municipalities, the Commissioner of Police, the Director of Prohibition and Excise, the District Magistrates and the Election Commission, Election Tribunals, Returning Officers and other authorities under the Election Commission.

GUJARAT POLLUTION CONTROL BOARD

NOTIFICATION

Gandhinagar, 12th December, 2019.

No: GPCB/P-1/218(A)/530582: The Gujarat Pollution Control Board in exercise of the powers conferred under clause (d) of Section (2) of the Air (Prevention and Control of Pollution) Act 1981, hereby makes the following amendments in the Gujarat Government Gazette notification in Vol. LVIII on Friday October 27, 2017 and Vol. LIX, Tuesday February 6, 2018.

- (A) In the serial no. (1) of (3) list of approved fuels, "Furnace oil (FO)" is deleted for new Project/Permission.
- (B) The serial no. (2) of notification dated 27.10.2017 and serial no. (B) of notification dated 06.02.2018 shall be replaced and read as under for new Project/Permission:
- (1) Petcoke is hereby notified as "APPROVED FUEL" subject to the following conditions:-
- a) The Sulphur content shall not be more than 7% in any case/ circumstance.
- b) Petcoke shall be permitted in the following projects only:-
- i. Cement manufacturing in kilns.
- ii. Glass manufacturing- up to 25 % of total fuel consumption.
- (C) The new project in the sector mentioned above in serial number (1)(b), using Petcoke or Furnace Oil (FO) as a fuel shall not be permitted in Non-attainment cities declared by the Central Pollution Control Board, New Delhi.

N. M. TABHANI,
Member Secretary,
Gujarat Pollution Control Board,
Gandhinagar.

GOVERNMENT CENTRAL PRESS, GANDHINAGAR